

Perfect Protection For Rack-Mount Systems

The PRO-RT Series is a value-priced, yet feature-rich UPS incorporating line-interactive technology that preserves battery power by providing voltage regulation during brownouts or voltage sags. The PRO-RT Series can be used to support servers, telecom or VoIP systems, security systems, plus many other applications.

An LCD display provides visual notification of power status, including input voltage, frequency, percent of battery charge, estimated runtime, plus many other conditions.

Versatile Communications

Each PRO-RT model includes Minuteman's SentryPlus® power management and diagnostic software. When installed on a workstation or server, the user gains complete control over monitoring and managing the UPS using a convenient web browser-based interface. The SentryPlus software communicates via a built-in USB port or through a RS-232 connector on the UPS. In addition, managing the UPS within a Network Management System (NMS) is easy with the installation of an optional SNMP card.

Designed for versatility, the PRO-RT models can be mounted in a standard rack using the included rackmount ears. These ears can also be attached to the unit to allow it to stand as a tower. An optional kit is available for mounting the unit to a wall.

High-end Features - Budget Friendly Price

The PRO-RT offers many features normally found on higher priced models, including an LCD status display which shows the following:

- **Input / Output voltage and frequency**
Monitor the status of your utility power
- **UPS and battery mode / status**
Eliminate guesswork with straightforward display of the unit's status
- **Load capacity**
Load indicator shows how much electrical load is being placed on the unit
- **Estimated runtime based on connected load**
Find out how much backup time remains during a blackout right on the unit

*Excludes lead acid batteries

Capacity

- ☒ Small ☒ Midsize ☐ Enterprise level

Applications

- ☒ Network/Server ☒ VoIP Systems ☒ IP/Analog Phone & Security

In addition to the LCD display, the PRO-RT also offers:

- **Rack/tower installation**
(2U rack height) or wall mounting with optional kit
- **Minuteman SentryPlus Software**
SentryPlus auto-shutdown and monitoring software is included with every unit.
- **RS-232 and USB Communications**
No special USB drivers are required for USB communications. Both units are automatically recognized by Microsoft® Windows® as HID-compliant devices – similar to a mouse or a keyboard.
- **SNMP compatible**
Each PRO-RT unit can be managed on a network with the addition of an optional SNMP management card.
- **Fax/Modem/Network Line Protection**
The PRO-RT UPS provides a low cost means of protecting fax/modem/network lines.
- **RoHS Compliant**
All PRO-RT products are manufactured using non-hazardous* materials making them safer for the environment and a green-friendly addition to any data center.
- **Warranty**
Each PRO-RT UPS system is covered by a three-year parts and labor warranty and \$100,000 Minuteman Platinum Protection Plan® (U.S.A. and Canada only).



Minuteman® PRO-RT™ Series Line-Interactive UPS Specifications

Model Number	PRO1000RT		PRO1500RT	
VA Rating	1000VA		1500VA	
Max Output Power	700Watts		1050Watts	
Output Receptacles	(6) NEMA 5-15R Battery & surge (2) NEMA 5-15R Surge only		(6) NEMA 5-15R Battery & surge (2) NEMA 5-15R Surge only	
Input Connection	10 ft. Power cord with NEMA 5-15P			
Input (non-battery operation)				
Voltage Range	90 to 150VAC			
Frequency Range	50/60Hz ±5Hz, auto-sensing			
AC Leakage Current	<1.0mA at full rated non-linear load			
Input Protection	Resettable circuit breaker			
Output (non-battery operation)				
Voltage Range	104 to 132VAC			
Frequency	50/60Hz ±5Hz			
Efficiency (AC-AC)	>90% at full rated non-linear load			
Output (battery operation)				
Voltage	120VAC			
Voltage Regulation	Nominal ±5% until low battery warning			
Frequency	50/60Hz, ±0.5Hz (unless synchronized to utility)			
Wave Form	Simulated sine wave			
Typical Transfer Time	6-10 ms (max 10ms)			
Overload Capacity	110% for 10 seconds, 120% shutdown immediately			
Protection	Over-current, short-circuit protected, and latching shutdown			
Estimated Runtimes - Full /Half Load	5 min. / 16 min.		5 min. / 17 min.	
Battery System				
Hot Swappable Battery	Yes			
Internal Battery Module	BM0043		BM0044	
DC Leakage Current	<30uA (±10uA) with no AC applied and the unit in the off position			
Battery Type	Sealed, non-spillable, maintenance-free, valve-regulated lead acid			
Surge Protection				
Surge Energy rating	1140 joules			
Surge Current Capacity	6500 Amps total			
Surge Response Time	0-ns (instantaneous) normal mode; <5ns common mode			
Certifications				
Agency Approvals	cTUVus (conforms to UL1778, CSA 22.2 standards), CE			
EMI/RFI Filtering	FCC Part 15 Class B, EN5022, EN61000-6-1, EN61000-6-3, EN61000-4-5			
Environmental				
Temperature : Operating (Storage)	0° to +40°C / +32° to +104°F (-15° to +45°C / +5° to 113°F)			
Humidity: Operating & Storage	0 to 95% non condensing			
Elevation: Operating (Storage)	0 to +3,000 m / 0 to +10,000 ft (0 to +15,000 m / 0 to +50,000 ft)			
Physical				
Weight: Lbs/Kgs	35.1 / 15.9		43.0 / 19.5	
Dimensions (H x W x D): Inch/mm	3.5" x 17.3" x 15.7" / 89 x 440 x 398			



PRO-RT Series Features

- 1 LCD Status Display
- 2 Rack/Tower Convertible Mounts
- 3 USB and RS-232 Ports
- 4 Phone/Fax/Network Port
- 5 SNMP Accessory Panel
- 6 Six (6) Battery & Surge Outlets
- 7 Two (2) Surge-only Outlets
- 8 10 ft. Input Power Cord



© Copyright 2012, Para Systems, Inc. Product specifications are subject to change without notice. Minuteman and Minuteman Platinum Protection Plan are registered trademarks and PRO-RT and SentryPlus are trademarks of Para Systems, Inc.

PN-34000406 - 2-12



Para Systems, Inc. | Minuteman Power Technologies
 1455 LeMay Drive | Carrollton, Texas 75007 | 972.446.7363 | 800.238.7272
www.minutemanups.com | www.sizemyups.com